

Technical Data Sheet

DES-PDM M

Round cable entry plates with internal frame and locknut

- ▶ For several number of non-terminated cables
- ▶ High retaining force thanks to the double membrane
- ▶ Cost efficient solution
- ▶ High IP grade (IP65-66-68)
- ▶ Metric sized



The round metric DES-PDM M is an innovative alternative to standard cable glands on electrical, electronic and telecommunication cabinets and equipment.

The cable is pushed through the front membrane, whilst the second membrane increases the strain relief and liquid resistance.

Technical data

Material: TPE

Flammability: self-extinguishing acc. to UL94-V0

Temperature: -40°C... +105°C (static)

Features: halogens and silicones free

Related products

Hydraulic punch driver HY360

Model	Code	Cable nr. - Ø cables min/max [mm]	Thread x1.5	Dimensions Ø P [mm]	Pcs /pack
DES-PDM M	1732033204 1732034205	3 - 2.6 / 6.5 1 - 5.5 / 12.5			
DES-PDM M	1732033242 1732034252	4 - 3.5 / 8.8	M32	46	10
DES-PDM M	1732033207 1732034208	7 - 2.6 / 6.5			
DES-PDM M	1732034008 1732035009	4 - 2.6 / 6.5 4 - 4 / 10.2	M40	54	10
DES-PDM M	1732035008 1732036009	5 - 4.6 / 10.2 3 - 6.8 / 12.5			
DES-PDM M	1732035010 1732036011	7 - 2.8 / 6.5 2 - 4.6 / 10.2 1 - 14.5 / 22	M50	64	10
DES-PDM M	1732035012 1732036013	4 - 2.8 / 6.5 8 - 4.6 / 10.2			
DES-PDM M	1732035019 1732036020	19 - 2.8 / 6.5			
DES-PDM M	1732036309 1732037310	1 - 2.6 / 6 3 - 4.6 / 10.2 4 - 8.6 / 16.2 1 - 10.9 / 20			
DES-PDM M	1732036313 1732037314	4 - 2.8 / 6 4 - 4.6 / 10.2 5 - 9.5 / 16.2	M63	77	10
DES-PDM M	1732036314 1732037315	14 - 5 / 10			
DES-PDM M	1732036335 1732037336	35 - 2.6 / 5.5			

Double membrane



Dimensions [mm]

