
















Technical Data Sheet

 	Flexible heavy conduit	 	Nr.: 0243. ... Revision B5 Nov 2017
	ROHRflex® PA 12-SD		

Dimensions							
 Fine profile  Coarse profile				Smallest bending radius stat. > static (fixed) dyn. > dynamic			
Part No.	AD OD						
Color:	∅	mm	stat	dyn	kg/m	m	
Black							
 Fine Profile							
0243.202.006	10,0	6,0 x 10,0	15	35	0,023	50	
0243.202.010	13,0	9,5 x 13,0	25	45	0,032	50	
0243.202.012	15,8	11,5 x 15,8	35	55	0,039	50	
0243.202.016	21,2	16,0 x 21,2	50	85	0,073	50	
 Coarse Profile							
0243.232.016	21,2	15,0 x 21,2	50	112	0,079	50	
0243.232.023	28,5	21,5 x 28,5	60	120	0,120	50	
0243.232.029	34,5	27,0 x 34,5	70	140	0,168	25	
0243.232.036	42,5	35,0 x 42,5	80	170	0,190	25	
0243.232.048	54,5	46,5 x 54,5	100	190	0,240	25	

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.