












## Technical Data Sheet

	<b>IP 40</b>	<b>Flexible conduit</b>	Nr.: 0261.242 ...  June 2020
	<b>ROHRflex® PA 6-LG</b>		

Description			
<b>Material</b>	Modified Plastic (PA6)	<b>Temperature range</b>	<b>Construction</b>
<b>Color</b>	Black	-25°C up to + 120°C -13°F up to + 248°F	Corrugated all-plastic tubing, slitted, internally and externally corrugated

Dimensions						
 Fine profile				<b>Smallest bending radius</b> stat. > static (fixed) dyn. > dynamic		
<b>Part No.</b>	AD OD	 mm	 stat	 dyn	 kg/m	 m
<b>Color:</b> Black	∅	mm	stat	dyn	kg/m	m
 fine profile						
0261.242.006	10,0	6,5 x 10,0	13	35	0.020	50
0261.242.010	13,0	10,0 x 13,0	20	45	0.024	50
0261.242.012	15,8	12,0 x 15,8	35	55	0.034	50
0261.242.016	21,2	16,5 x 21,2	45	75	0.056	50
0261.242.023	28,5	22,0 x 28,5	55	100	0.100	50
0261.242.029	34,5	27,5 x 34,5	65	120	0.122	25
0261.242.036	42,5	35,5 x 42,5	90	150	0.145	25
0261.242.048	54,5	48,0 x 54,5	100	190	0.225	25