

### In and on the machine (Static Applications)

- |               |   |
|---------------|---|
| CES           | Cable entry systems designed to manage cable entry into machines and panels <ul style="list-style-type: none"><li>• Options for pre-terminated and non-terminated cables</li><li>• Up to NEMA 4X / IP 66 rated protection</li><li>• Robust frame and insert options with integrated gaskets</li></ul> |
| ROHRflex PA6  | Medium-duty corrugated conduit for static applications <ul style="list-style-type: none"><li>• Good flexibility, good impact and compression resistance</li><li>• UL94VO rated / highly self-extinguishing</li></ul>  |
| ROHRflex PA6L | Medium duty corrugated economical conduit for static applications <ul style="list-style-type: none"><li>• Good flexibility, good impact and compression resistance</li><li>• UL94HB rated / flame retardant</li></ul>   |



### In and on the machine (Automation/Robotic / Dynamic Applications)

- |                 |  |
|-----------------|--|
| ROHRflex PA12   | Medium-duty corrugated conduit for dynamic applications <ul style="list-style-type: none"><li>• Excellent flexibility and fatigue / reversed bending</li><li>• Excellent UV protection</li></ul> |
| ROHRflex PA12-D | Heavy-duty corrugated conduit for dynamic applications <ul style="list-style-type: none"><li>• High impact and compression resistance</li><li>• Excellent flexibility</li></ul>                  |

### To and from the Machine

- |                    |   |
|--------------------|---|
| ROHRflex PA6-D     | Heavy-duty corrugated conduit for static applications <ul style="list-style-type: none"><li>• High impact and compression resistance</li><li>• UL94VO rated / highly self-extinguishing</li></ul> |
| ROHRflex PA6-UL-SD | <ul style="list-style-type: none"><li>• UL Listed, NFPA 70 / ANSI Article 356 / NEC approved conduit</li><li>• Excellent mechanical and impact strength</li><li>• UL94V2 rated</li></ul>          |



### Other Options

- |                |   |
|----------------|---|
| ROHRflex Multi | Large sized conduit for cable bundling <ul style="list-style-type: none"><li>• Available in PA6 (static) and PA 12 (dynamic)</li><li>• Available in 3" and 4" sizes</li></ul> |
| FLEXAzip       | Retro-fitting conduit, slitted and re-closeable <ul style="list-style-type: none"><li>• Ideal for static applications</li><li>• UL94HB rated</li></ul>                        |
| ROHRflex DUO   | Two-piece retrofitting conduit <ul style="list-style-type: none"><li>• Available in PA6 and PP</li><li>• Ideal for static applications</li><li>• UL94HB rated</li></ul>       |

All AerosUSA conduits are free from halogens and cadmium and are non-corrosive. Available connectors up to IP69K protection. Other alternative products may be available depending on project and application. For technical details and specifications please visit [www.aerosusa.com](http://www.aerosusa.com)



*"Unsurpassed in Cable Protection and Strain Relief"*

2409 Herr St.  
Harrisburg, PA 17103

### Outdoor Applications

- **IP68/69K fittings with plastic bodies, available in NPT, Metric and PG threads\***  
Metal thread: Straight (RQGK), 90° (RQBK90/DR), 45° (RQBK45/DR)  
Plastic thread: Straight (RQG), 90° (RQW 90, RQW-F), 45° (RQB 45)
- **IP68/69K fittings with strain relief, available in Metric and PG threads, EMC shielding is available**  
Metal thread: Straight (RQGKZ, RQGKZP, RQGKZE, RQGKZED(EMC)),  
Plastic thread: Straight (RQGZ)
- **IP68/69K fittings with female thread, available in NPT, Metric, PG and UNEF threads**  
Metal thread: Straight (RQGK2)  
Plastic thread: Straight (RQG2)
- **IP68/69K Y, T, Coupling, Fitting reducer**  
Y (RQY-PA), T (RQT-PA), Coupler (RQK-PA, RQK-GW-PA), Reducer (RQGR)
- **Accessories**  
Abrasion ring (RQPRO)  
Clamps (RQM, RQS, RQHG, RQH)
- **Cable Entry Systems**  
Designed to manage cable entry into panels. Accepts pre- and non-terminated cables. Up to NEMA 4X / IP 66 rated
- **Cable Glands**  
Wide range of nylon and metallic options including EN 45545-3 requirements. Up to IP 68 rated.  
Progress MS, Syntec, Progress MS EMV

### Indoor Applications

- **IP66 fittings with plastic bodies and threads, available in NPT, Metric and PG threads**  
Straight (RQG1), 90° (RQW1 90, RQB1 90), 45° (RQB1 45)  
Straight with strain relief (RQGZ1)
- **IP66 fittings with plastic female thread, available in Metric and UNEF threads**  
Straight (RQG3)
- **IP65 economical fittings with plastic bodies and threads, available in NPT, Metric and PG threads**  
Straight (RQLG1), 90° (RQLB1 90), 45° (RQLB1 45)
- **Accessories**  
Y (RQY), T (RQT), Coupler (RQK), End sleeves (RQA, RQE)



\*UL Listed sizes available.

All AerosUSA fittings are free from halogens and cadmium. Connectors available up IP65 - IP69K protection and jumbo oversized fittings for 3" & 4" conduits. Other alternative products may be available depending on project and application. For technical details and specifications please visit [www.aerosusa.com](http://www.aerosusa.com)



*"Unsurpassed in Cable Protection and Strain Relief"*

2409 Herr St.  
Harrisburg, PA 17103