



Superstructure / Crew and Passenger Compartments (Indoor Applications)

ROHRflex PA6 Medium-duty corrugated conduit for static applications

Good flexibility, good impact and compression resistance

UL94VO rated / highly self-extinguishing

ROHRflex PA6L Medium duty corrugated economical conduit for static applications

• Good flexibility, good impact and compression resistance

• UL94HB rated / flame retardant

CES Cable Entry Systems designed to manage cable entry into control panels

• Options for pre-terminated and non-terminated cables

• Up to NEMA 4X / IP66 rated protection

Robust frame and insert options with integrated gaskets

Open Deck / Cargo Compartment and Engine Room (Outdoor Applications)

ROHRflex PA12 Medium-duty corrugated conduit for dynamic applications

Highly flexible and reverse bending strength

Excellent UV protection

ROHRflex PA6-D Heavy-duty corrugated conduit for static applications

High impact and compression resistance

• UL94VO rated / highly self-extinguishing



On Masts and Booms / Movable Systems (Outdoor Applications)

ROHRflex PA12 Medium-duty corrugated conduit for dynamic applications

Highly flexible and reverse bending strength

Excellent UV protection

Power Engines

ROHRflex PA6L Medium duty corrugated economical conduit for static applications

- Good flexibility, good impact and compression resistance
- UL94HB rated / flame retardant

Fire Safety Certificates available according to: IRIS Certification, EN 45545-2 (HL-3), NFPA 130 / ASTM E662, SMP800-C **Shipbuilding Certificates**: Lloyd's Register, DNV-GL







All AerosUSA conduits are free from halogens and cadmium and are non-corrosive. Available connectors up to IP69K protection. Other alternative products may be available depending on project and application. For technical details and specifications please visit www.aerosusa.com



"Unsurpassed in Cable Protection and Strain Relief"



Fittings /Supports for Cable & Conduit Applications

Aerosusa.com service@aerosusa.com 855.393.9905

Outdoor Applications

 IP68/69K fittings with plastic bodies, available in NPT, Metric and PG threads*

Metal thread: Straight (RQGK), 90° (RQBK90/DR), 45° (RQBK45/DR) Plastic thread: Straight (RQG), 90° (RQW 90, RQW-F), 45° (RQB 45)

 IP68/69K fittings with strain relief, available in Metric and PG threads, EMC shielding is available

Metal thread: Straight (RQGKZ, RQGKZP, RQGKZE, RQGKZED(EMC)),

Plastic thread: Straight (RQGZ)

 IP68/69K fittings with female thread, available in NPT, Metric, PG and UNEF threads

Metal thread: Straight (RQGK2) Plastic thread: Straight (RQG2)

IP68/69K Y, T, Coupling, Fitting reducer

Y (RQY-PA), T (RQT-PA), Coupler (RQK-PA, RQK-GW-PA), Reducer (RQGR)

Accessories

Abrasion ring (RQPRO)
Clamps (RQM, RQS, RQHG, RQH)

• Cable Entry Systems

Designed to manage cable entry into panels. Accepts pre- and non-terminated cables. Up to NEMA 4X / IP 66 rated

Cable Glands

Wide range of nylon and metallic options including EN 45545-3 requirements. Up to IP 68 rated.
Progress MS, Syntec, Progress MS EMV

Indoor Applications

 IP66 fittings with plastic bodies and threads, available in NPT, Metric and PG threads

Straight (RQG1), 90° (RQW1 90, RQB1 90), 45° (RQB1 45) Straight with strain relief (RQGZ1)

 IP66 fittings with plastic female thread, available in Metric and UNEF threads

Straight (RQG3)

Accessories

Y (RQY), T (RQT), Coupler (RQK), End sleeves (RQA, RQE)



*UL Listed sizes available.

All AerosUSA fittings are free from halogens and cadmium. Connectors available up IP65 - IP69K protection and jumbo oversized fittings for 3" & 4" conduits. Other alternative products may be available depending on project and application. For technical details and specifications please visit www.aerosusa.com



"Unsurpassed in Cable Protection and Strain Relief"