

Technical Data Sheet

ROHRflex-MULTI PA 6

ROHRflex corrugated plastic tubings


Protective all-plastic tubing, internally and externally corrugated, for large quantity of cables

Temperature: -40°C ... +120°C ^ +150°C
-40°F ... +248°F ^ +302°F

Material: PA 6 plastics

Characteristics:

- Properties: non-crush
- Air and liquid tight
- Free of silicone, cadmium, halogen
- Flame retardant
- UV-resistant
- Oil resistant up to 80C
- Benzine resistant
- Widely resistant to acid and solvents



Applications:

- Machine and plant constructions, automotive, railway industry, shipbuilding, automation, electrical installations



Characteristics	Unit	Value	Test
Mechanical characteristics			
Resistance to compression	N		EN 61386-23
Resistance to impact (-45C)	J		EN 61386-23
Resistance to bending		flexible	EN 61386-23
Flame characteristics			
Free of halogen and phosphor		yes	DIN 53474
Flame class		HB	UL 94
Resistance to flame propagation		non flame propagating	EN 61386-23
Railway EN 45545-2			
Oxygen index	%		ISO 4589-2
Specific characteristics			
Resistance to fuels, mineral oil, fat alkalises, glycols, acids, bases		excellent	
System test			
Pull-out resistance with FLEXAquick	N		EN 61386-23


Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.

Technical Data Sheet

ROHRflex-MULTI PA 6

ROHRflex corrugated plastic tubings

Protective all-plastic tubing, internally and externally corrugated, for large quantity of cables



Part Number	Color	Trade Size mm in	Profile	ID mm in	OD mm in	BR Stat. mm in	BR Dyn. mm in	Weight kg/m lb/ft	Std Pack m ft
0206.202.056	Black	56.0 2 1/2	Fine	56.3 2.22	67.2 2.65	130 5.12	270 10.63	0.46 0.31	10 32
0206.202.070	Black	70.0 3	Fine	66.5 2.62	79.2 3.12	170 6.69	350 13.78	0.50 0.34	10 32
0206.202.095	Black	95.0 4	Fine	91.0 3.58	106.0 4.17	225 8.89	450 17.72	0.95 0.64	10 32
0206.201.070	Gray	70.0 3	Fine	66.5 2.62	79.2 3.12	170 6.69	350 13.78	0.50 0.34	10 32
0206.201.095	Gray	95.0 4	Fine	91.0 3.58	106.0 4.17	225 8.89	450 17.72	0.95 0.64	10 32

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.